



| | |
|-----------------------------------|--|
| Construction | Tufted Loop Pile Carpet |
| Yarn | 100% Stainproof Miracle Fibre |
| Width | 4.0m |
| Standard Roll Length | 30m |
| Yarn Weight | 1020g/m ² (30oz/yd ²) |
| Total Weight | ± 2252g/m ² |
| Pile Height | ± 7.0mm |
| Total Thickness | ± 9.0mm |
| Machine Gauge | 5/16" |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | FusionBac |
| Electrical Properties | Antistatic |
| Fire Rating | SANS 10177-4 |
| VOC Rating | ASTM D5116 |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Underfloor Heating | Suitable |
| Stair Rating | Suitable |
| Rating | Heavy Duty Residential |
| Warranties | 10 Year Residential Warranty |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. |
| Environmental | GreenStar Eco-Wash™ Treatment Low VOC, Solution dyeing uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001 |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.