# Immerse

| | |
|---|---|
| **Construction** | Tufted Loop Pile Carpet |
| **Yarn** | 100% Stainproof Miracle Fibre |
| **Width** | 4.0m |
| **Standard Roll Length** | 30m |
| **Yarn Weight** | 1020g/m² (30oz/yd²) |
| **Total Weight** | ± 2252g/m² |
| **Pile Height** | ± 7.0mm |
| **Total Thickness** | ± 9.0mm |
| **Machine Gauge** | 5/16” |
| **Primary Backing** | Woven Polypropylene |
| **Secondary Backing** | FusionBac |
| **Electrical Properties** | Antistatic |
| **Fire Rating** | SANS 10177-4 |
| **VOC Rating** | ASTM D5116 |
| **Anti-allergenic Properties** | Will not shed or pill. Resistant to mould & mildew. |
| **Underfloor Heating** | Suitable |
| **Stair Rating** | Suitable |
| **Rating** | Heavy Duty Residential |
| **Warranties** | 10 Year Residential Warranty |
| **Installation** | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>All seams must be sealed.<br>Must be laid in accordance with AS/NZ Installation Standards. |
| **Environmental** | GreenStar<br>Eco-Wash™ Treatment<br>Low VOC, Solution dying uses no water<br>Environmental Management ISO 14001<br>Quality Management ISO 9001<br>Occupational Health and Safety Management ISO 45001 |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.