

Category	European Hardened Timber
Type	3-layer Veneer: 1-strip
Plank Size	150mm x 1810mm
Planks per Carton	12pcs / 3.258m ²
Weight per Carton	20.80kg
Thickness	7.0mm
Top Layer Thickness	0.6mm
Surface Finishing	Matt Lacquer
Bevel	Microbevelled 4-sided
Core	HDF
Locking System	Woodloc® 5G
Slip Resistance	R10 (DIN 51130)
Thermal Resistance	0.0533 m ² K/W (EN 12667)
Thermal Conductivity	0.134 W/mK (EN 12664)
Fire Rating	CRF ≥ 6.75 kW/m ² (ISO 9239-1)
Formaldehyde Group	E1 (EN717-1)
Indoor Air Quality	A+ Emissions / Indoor Air Comfort Gold® FloorScore®
Wear Resistance	>6000 Cycles (EN 14354)
Impact Resistance	EC3 (EN 14354)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Performance Classification	Class 1 (EN 350-2)
Use Area	Heavy Domestic Moderate Commercial
Stair Rating	Suitable
Warranties	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
Installation	Must be properly installed according to the installation instructions. Glue down installation: please contact MBP (NZ) Ltd for Mapei adhesive recommendation and install instructions.
Environmental	Environmental Management ISO 14001 Quality Management ISO 9001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.