



Construction	Tufted Multi Scroll Loop Pile								
Yarn	100% Stainproof Miracle Fibre (Polypropylene)								
Size	500mm x 500mm								
Tiles per Carton	20pcs / 5.0m ²								
Pile Weight	500g/m ²								
Total Weight	4223g/m ²								
Pile Height	2.5mm								
Total Thickness	7.5mm								
Machine Gauge	1/10th								
Backing	EcoBac								
Electrical Properties	Antistatic								
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)								
Fire Rating	CRF 3.9wkW/m ² (ISO 9239-1)								
VOC Rating	Pass (GBCSA/GLP Criteria)								
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.								
Colour Fastness	<table border="0"> <tr> <td>Light</td> <td>7 (ISO 105 - B02)</td> </tr> <tr> <td>Rubbing</td> <td>Wet 4 - 5 (ISO 105 - X12)</td> </tr> <tr> <td></td> <td>Dry 4 - 5 (ISO 105 - X12)</td> </tr> <tr> <td>Water</td> <td>4 - 5 (ISO 105 - E01)</td> </tr> </table>	Light	7 (ISO 105 - B02)	Rubbing	Wet 4 - 5 (ISO 105 - X12)		Dry 4 - 5 (ISO 105 - X12)	Water	4 - 5 (ISO 105 - E01)
Light	7 (ISO 105 - B02)								
Rubbing	Wet 4 - 5 (ISO 105 - X12)								
	Dry 4 - 5 (ISO 105 - X12)								
Water	4 - 5 (ISO 105 - E01)								
Underfloor Heating	Suitable								
Rating	Medium Duty Commercial								
Stair Rating	Suitable								
Warranties	15 Year Commercial Warranty								
Installation	<p>Laying recommendation: Monolithic</p> <p>Please contact Gilt Edge Industries for all adhesive and installation instructions.</p> <p>NB: If recommended adhesive is not used, claims will not be accepted.</p> <p>Must be laid in accordance with AS/NZ Installation Standards.</p>								
Environmental	<p>GreenStar, Low VOC</p> <p>Solution dyeing uses no water</p> <p>Quality Management ISO 9001</p> <p>Environmental Management ISO 14001</p> <p>Occupational Health and Safety Management ISO 45001</p>								



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.