



Construction	Tufted Multi Scroll Loop Pile	
Yarn	100% Stainproof Miracle Fibre (Polypropylene)	
Size	500mm x 500mm	
Tiles per Carton	20pcs / 5.0m ²	
Pile Weight	500g/m ²	
Total Weight	4223g/m ²	
Pile Height	2.5mm	
Total Thickness	7.5mm	
Machine Gauge	1/10th	
Backing	EcoBac (with Bitumen layer)	
Impact Sound Reduction	ΔLw 28dB (EN ISO 10143-3)	
Electrical Properties	Antistatic	
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)	
Fire Rating	CRF 3.9kW/m ² (ISO 9239-1)	
VOC Rating	Pass (GBCSA/GLP Criteria)	
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.	
Colour Fastness	Light	7 (ISO 105 - B02)
	Rubbing	Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12)
	Water	4 - 5 (ISO 105 - E01)
Underfloor Heating	Suitable	
Rating	Medium Duty Commercial	
Stair Rating	Suitable	
Warranties	15 Year Commercial Warranty	
Installation	Laying recommendation: Monolithic Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	
Environmental	GreenStar Low VOC, Solution dying uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001 Science Based Targets Institute	



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.