Kamio

Belgotex[®]



Construction	Tufted Multi Scroll Loop Pile
Yarn	Stainproof Miracle Fibre (Polypropylene)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Pile Weight	500g/m ²
Total Weight	± 4223g/m ²
Pile Height	2.5mm
Total Thickness	7.0mm
Machine Gauge	1/10th
Backing	EcoBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Fire Rating	CRF 3.9kW/m ² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Colour Fastness	Light 7 (ISO 105 - B02) Rubbing Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12) Water 4 - 5 (ISO 105 - E01)
Classification	Medium Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar Low VOC, solution dying uses no water. ISO 14001.
Installation	Laying recommendation: Monolithic Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

B.