

# Landform



|                                   |   |
|-----------------------------------|---|
| <b>Construction</b>               | Tufted Pattern Colour Placement Loop Pile   |
| <b>Yarn</b>                       | 100% Stainproof SDX (Solution dyed nylon)   |
| <b>Size</b>                       | 1000mm x 250mm  |
| <b>Tiles per Carton</b>           | 20pcs / 5.0m <sup>2</sup>   |
| <b>Pile Weight</b>                | 650g/m <sup>2</sup>   |
| <b>Total Weight</b>               | 2520g/m <sup>2</sup>  |
| <b>Pile Height</b>                | ± 5.5 mm (±0.5)   |
| <b>Total Thickness</b>            | ± 7.5 mm (±0.5)   |
| <b>Machine Gauge</b>              | 1/10th  |
| <b>Backing</b>                    | Probac (bitumen free)   |
| <b>Impact Sound Reduction</b>     | ΔLw 26dB (EN ISO 10143-3)   |
| <b>Sound Absorption</b>           | aw: 0.25 (ISO 354:2003)   |
| <b>Electrical Properties</b>      | Antistatic  |
| <b>Electrical Propensity</b>      | ≤ 2kV (ISO 6356: 2012)  |
| <b>Thermal Resistance</b>         | 0.1229 m <sup>2</sup> .K/W (ISO 8302)   |
| <b>Fire Rating</b>                | CRF 8.1kW/m <sup>2</sup> (ISO 9239-1)   |
| <b>VOC Rating</b>                 | Pass (ASTM D5116: 2017)   |
| <b>Colour Fastness Light</b>      | >6 (ISO 105 - B02)  |
| <b>Rubbing (staining)</b>         | 4-5 (ISO 105 - X12)   |
| <b>Water (staining)</b>           | 4-5 (ISO 105 - E01)   |
| <b>Anti-allergenic Properties</b> | Will not shed or pill. Resistant to mould & mildew.   |
| <b>Underfloor Heating</b>         | Suitable  |
| <b>Rating</b>                     | Heavy Duty Commercial   |
| <b>Stair Rating</b>               | Suitable  |
| <b>Warranties</b>                 | 15 Year Commercial Warranty   |
| <b>Installation</b>               | Laying recommendation: Ashlar, Brick, Monolithic, Herringbone or Tessellated<br>Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>Must be laid in accordance with AS/NZ Installation Standards. |
| <b>Environmental</b>              | GreenTag Product Health Declaration (PHD) Platinum Health Certified<br>Eco-Wash™ Treatment<br>Low VOC, Solution dying uses no water<br>Quality Management ISO 9001<br>Environmental Management ISO 14001<br>Occupational Health and Safety Management ISO 45001   |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices