

# Mipolam Affinity



|                                                             |                                                                                                                                                                                                                                                                                |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>                                         | Homogeneous Sheet Vinyl                                                                                                                                                                                                                                                        |
| <b>Width</b>                                                | 2.0m                                                                                                                                                                                                                                                                           |
| <b>Standard Roll Length</b>                                 | 20m                                                                                                                                                                                                                                                                            |
| <b>Pattern Repeat</b>                                       | Random repeat, directional laying                                                                                                                                                                                                                                              |
| <b>Total Weight</b>                                         | 2850g/m <sup>2</sup>                                                                                                                                                                                                                                                           |
| <b>Wear Layer Thickness</b>                                 | 2.0mm                                                                                                                                                                                                                                                                          |
| <b>Total Thickness</b>                                      | 2.0mm                                                                                                                                                                                                                                                                          |
| <b>Surface Protection</b>                                   | Easycare™                                                                                                                                                                                                                                                                      |
| <b>Slip Resistance - Oil Pendulum</b>                       | R10 (AS4586:2013)                                                                                                                                                                                                                                                              |
| <b>Slip Resistance - Wet Pendulum</b>                       | P5 (AS4586:2013, App A)                                                                                                                                                                                                                                                        |
| <b>Electrical Propensity</b>                                | ≤ 2kV (EN 1815)                                                                                                                                                                                                                                                                |
| <b>Fire Rating</b>                                          | CRF 9.8kW/m <sup>2</sup> (ISO 9239-1)                                                                                                                                                                                                                                          |
| <b>Acoustic Insuation</b>                                   | 5dB (ISO 717-2)                                                                                                                                                                                                                                                                |
| <b>Wear Resistance</b>                                      | ≤2mm <sup>3</sup> (EN 660.2)                                                                                                                                                                                                                                                   |
| <b>Wear Group</b>                                           | T (NF 189)                                                                                                                                                                                                                                                                     |
| <b>Type Binder Content</b>                                  | II (EN ISO 10581)                                                                                                                                                                                                                                                              |
| <b>Dimensional Stability</b>                                | ≤0.40% (EN ISO 23999, EN 434)                                                                                                                                                                                                                                                  |
| <b>Thermal Insulation</b>                                   | 0.25W/mK (ISO 10456)                                                                                                                                                                                                                                                           |
| <b>Indoor Air Quality</b>                                   | TVOC after 28 days <10µg/m <sup>3</sup> (ISO 16000-6)<br>FloorScore®                                                                                                                                                                                                           |
| <b>Anti-bacterial Activity (E. coli - S. aureus – MRSA)</b> | > 99% inhibits growth (ISO 22196)                                                                                                                                                                                                                                              |
| <b>Underfloor Heating</b>                                   | Suitable up to 27°C                                                                                                                                                                                                                                                            |
| <b>Residual Indentation</b>                                 | ≈0.02mm (EN ISO 24343-1, EN 433)                                                                                                                                                                                                                                               |
| <b>Colour Fastness</b>                                      | ≥6 (EN 20 105 - B02)                                                                                                                                                                                                                                                           |
| <b>Chemical Resistance</b>                                  | OK (EN ISO 26987)                                                                                                                                                                                                                                                              |
| <b>Classification</b>                                       | Class 34 Commercial Very Heavy<br>Class 43 Industrial Heavy                                                                                                                                                                                                                    |
| <b>Warranties</b>                                           | 12 Year Commercial Warranty                                                                                                                                                                                                                                                    |
| <b>Installation</b>                                         | Cove fillet is required on all installations.<br>Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>Must be laid in accordance with AS/NZ Installation Standards. |
| <b>Environmental</b>                                        | 100% REACH Compliant<br>100% Recyclable<br>Greentag Certified<br>Environmental Product Declaration                                                                                                                                                                             |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

## Belgotex®

## A World of Perfect Choices