

| | |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction | Wall Covering |
| Width | 2.0m |
| Standard Roll Length | 20m / 40m ² |
| Total Weight | 1750g/m ² |
| Total Thickness | 2.0mm |
| Surface Protection | PUR Protect |
| Fire Rating | AS 5637.1-2015 |
| Dimensional Stability | ≤0.40% (ISO 23999, EN 434) |
| Anti-bacterial Activity (E. coli - S. aureus - MRSA) | > 99% inhibits growth (ISO 22196) |
| Residual Indentation | ≤0.10mm (EN 433) |
| Colour Fastness | ≥6 (EN 20 105 - B02) |
| Chemical Resistance | OK (EN 423) |
| Warranty | 10 Year Commercial Warranty |
| Environmental | 100% Recyclable |
| Installation | <p>Random Repeat, Reverse Sheet for Seaming Cove fillet is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.</p> |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.