

Construction	Wall Covering
Width	2.0m
Standard Roll Length	30m / 60m ²
Total Weight	1750g/m ²
Total Thickness	1.0mm
Surface Protection	PUR Protect
Fire Rating	AS 5637:1-2015
Dimensional Stability	≤0.40% (ISO 23999, EN 434)
Anti-bacterial Activity (E. coli - S. aureus - MRSA)	> 99% inhibits growth (ISO 22196)
Residual Indentation	≤0.10mm (EN 433)
Colour Fastness	≥6 (EN 20 105 - B02)
Chemical Resistance	OK (EN 423)
Warranty	10 Year Commercial Warranty
Environmental	100% Recyclable
Installation	<p>Random Repeat, Reverse Sheet for Seaming Cove fillet is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.</p>

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.