


| | |
|-----------------------------|---|
| Construction | Heterogeneous Sheet Vinyl |
| Width | 2.0m, 3.0m & 4.0m |
| Standard Roll Length | 30m |
| Pattern Repeat | Refer to Vinyl Range Statement |
| Total Weight | 1550g/m ² |
| Wear Layer Thickness | 0.25mm |
| Total Thickness | 2.5mm |
| Surface Protection | Natural Feel |
| Slip Resistance | R10 (DIN 51130) |
| Fire Rating | Cfl-S1 (EN 13501) |
| Acoustic Insulation | ΔLw 16dB (ISO 717-1) |
| Thermal Insulation | 0.25W/mK (ISO 10456) |
| Indoor Air Quality | A+ Emissions |
| Underfloor Heating | Suitable |
| Chemical Resistance | Very Good (EN ISO 26987) |
| Classification | Class 23 Domestic Heavy |
| Warranties | 7 Year Residential Warranty |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards. |
| Environmental | REACH Certificate of Compliance Quality Management ISO 9001 |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.