

Category	European Hardened Timber
Plank Size	233mm x 2050mm
Planks per Carton	5pcs / 2.388 m ²
Weight per Carton	16.71kg
Thickness	10mm
Top Layer Thickness	0.6mm
Surface Finishing	Super Matt
Bevel	Microbevelled 4-sided
Core	HDF
Locking System	Unifit X
Slip Resistance - Dry Pendulum	USRV 52.5 (CEN/TS 15676:2007 / EN 14342:2013)
Slip Resistance - Wet Pendulum	P5 (AS 4586-2013 Appendix A)
Thermal Resistance	Plank only: 0.073 m ² K/W (EN 12667) with Aqua Performance underlay: 0.141 m ² K/W with Aqua Elite underlay: 0.146 m ² K/W
Thermal Conductivity	0.14 W/mK (EN 12667)
Fire Rating	Cfl-s1, CRF ≥ 4.5 kW/m ² (EN 13501-1, ISO 9239-1)
Indoor Air Quality	Floorscore A+ Emissions
Formaldehyde Emissions	≤0.007 ppm, E1
Wear Resistance	> 6000 Cycles (EN14354)
Impact Resistance	EC3 (EN 14354)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Classification	Heavy Domestic Heavy Commercial
Stair Rating	Suitable
Warranties	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
Installation	Must be properly installed according to the installation instructions. Glue down installation: please contact MBP (NZ) Ltd for Mapei adhesive recommendation and install instructions.
Environmental	Forest Stewardship Council (FSC) Environmental Product Declaration LEED Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices