



| | |
|-----------------------------------|---|
| Construction | Tufted Multi Hi Low Loop Pile |
| Yarn | 100% Stainproof SDX (Solution Dyed Nylon) |
| Size | 500mm x 500mm |
| Tiles per Carton | 20pcs / 5.0m ² |
| Total Weight | ± 3450 g/m ² |
| Pile Height | 2.0 - 3.5mm |
| Total Thickness | ± 4.5mm |
| Machine Gauge | 1/10th |
| Backing | Bitumen |
| Electrical Properties | Antistatic |
| Electrical Propensity | < 2kV (EN 1307) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Acoustic Insulation | 18dB (EN/ISO 10143-3) |
| Acoustic Absorption | αω 0.15 (EN/ISO 354:2003) |
| Underfloor Heating | Suitable |
| Fire Rating | CRF 8.3kW/m ² (ISO 9239-1) |
| Fraying Behaviour | Pass (EN 1307) |
| Dimensional Stability | ≤ 0.2% (EN 1307) |
| Dimensions (Deviations) | 0.10% (EN 1307) |
| VOC Rating | Pass (GBCSA/GBCA) |
| Colour Fastness | Light 8 (ISO 105 - B02) Rubbing Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12) Water 4 - 5 (ISO 105 - E01) |
| Classification | Heavy Duty Commercial |
| Stair Rating | Suitable |
| Warranty | 15 Year Commercial Warranty |
| Environmental | Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water, ISO 14001 |
| Installation | Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.