

# Premium Compact



<b>Construction</b>	Heterogeneous Sheet Vinyl
<b>Width</b>	2.0m
<b>Standard Roll Length</b>	20m
<b>Total Weight</b>	2580g/m <sup>2</sup> - 2620g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	≥1.02mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	Evercare™
<b>Slip Resistance - Oil-Wet Ramp</b>	R10 (AS 4586:2013, App D)
<b>Slip Resistance - Wet Pendulum</b>	P4 (AS 4586-2013, App A)
<b>Electrical Propensity</b>	≤ 2kV (EN 1815)
<b>Fire Rating</b>	CRF 6.5kW/m <sup>2</sup> (ISO 9239-1)
<b>Impact Sound Reduction</b>	8dB (ISO 717-2)
<b>Wear Resistance</b>	≤2mm <sup>3</sup> (EN 660.2)
<b>Wear Group</b>	T
<b>Type Binder Content</b>	I (ISO 10582)
<b>Dimensional Stability</b>	≤0.40% (EN ISO 23999)
<b>Thermal Conductivity</b>	0.25W/mK (ISO 10456)
<b>Indoor Air Quality</b>	TVOC after 28 days <10µg/m <sup>3</sup> (ISO 16000-6) FloorScore®
<b>Anti-bacterial Activity (E. coli - S. aureus – MRSA)</b>	> 99% inhibits growth (ISO 22196)
<b>Residual Indentation (requirement)</b>	≤0.10mm (EN ISO 24343-1)
<b>Residual Indentation (average value measured)</b>	≈0.02mm
<b>Colour Fastness</b>	≥6 (EN ISO 105 - B02)
<b>Chemical Resistance</b>	OK (EN ISO 26987)
<b>Classification</b>	Class 34 Commercial Very Heavy Class 43 Industrial Heavy
<b>Warranties</b>	12 Year Commercial Warranty
<b>Installation</b>	Cove Fillet or Pencil Cove is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	Greentag Certified Environmental Product Declaration



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

# Belgotex®

A world of perfect choices\_