## Presidio

## Belgotex<sup>®</sup>























|     | $\smile$    |
|-----|-------------|
| S B | F- d- D1-44 |

Suitable For Underfloor Heating

| Construction               | Patterned Loop Pile  |
|----------------------------|--|
| Yarn                       | 100% Solution Dyed Nylon   |
| Size                       | 304.8mm x 1219.2mm   |
| Tiles per Carton           | 18pcs / 6.7m <sup>2</sup>  |
| Yarn Weight                | 949g/m²  |
| Pile Height                | 3.4mm  |
| Total Thickness            | 5.1mm  |
| Machine Gauge              | 1/10   |
| Primary Backing            | 100% Synthetic   |
| Secondary Backing          | Infinity Modular   |
| Electrical Properties      | Antistatic   |
| Electrical Propensity      | <3.0kv   |
| Fire Rating                | CRF 6.7 kW/m² (ISO 9239-1)   |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.  |
| Classification             | Heavy Duty Commercial  |
| Stair Rating               | Suitable   |
| Warranty                   | 15 Year Commercial Warranty<br>Limited Lifetime Wear & Backing<br>Limited 15-Year Xguard Stain Resistant<br>Limited 15-Year ColorSafe Bleach Resistant |
| Environmental              | GreenStar, Homestar™, LEED®<br>Well Building Standard®<br>CRI Green Label Plus Certified<br>Environmental Product Declaration                          |

ISO 14001

Contains Recycled content

Low VOC, solution dying uses no water

- Please contact Gilt Edge Industries for all adhesive and installation instructions.
- NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

Laying recommendation: 3-Step Verticle Ashlar or Herringbone.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Installation