

# Primero II



<b>Construction</b>	Luxury Vinyl Tile	
<b>Plank Size</b>	163mm x 988mm	
<b>Tiles per Carton</b>	24pcs / 3.87m <sup>2</sup>	
<b>Total Weight</b>	3726g/m <sup>2</sup>	
<b>Wear Layer Thickness</b>	0.3mm	
<b>Total Thickness</b>	2.25mm	
<b>Surface Protection</b>	Superguard®	
<b>Bevel</b>	4-sided micro-beve	
<b>Slip Resistance</b>	<b>Pattern</b>	<b>Slip Resistance (DIN 51130, AS NZS 4586:2013)</b>
	Evergreen Oak 22937	R9 / P3
	Major Oak 24847	R10 / P2
	Major Oak 24886	R10 / P2
	Major Oak 24982	R10 / P2
	Major Oak 24241	R10 / P2
	Summer Oak 24137	R10 / P2
	Summer Oak 24235	R10 / P2
	Summer Oak 24935	R10 / P2
	Summer Oak 24989	R10 / P2
<b>Electrical Propensity</b>	<2kV (EN 1815)	
<b>Electrical Resistance</b>	≤10 <sup>9</sup> Ohm (ISO 1081)	
<b>Fire Rating</b>	CRF 9.6kW/m <sup>2</sup> (ISO 9239-1)	
<b>Acoustic Insulation</b>	ΔLw 4dB (EN ISO 10140-3)	
<b>Residual Indentation</b>	≥0.10mm (ISO 24343-1)	
<b>Dimensional Stability</b>	≤0.05% (ISO 23999)	
<b>Thermal Insulation</b>	0.25w/(m.K) (EN 12524)	
<b>Thermal Resistance</b>	0.01m <sup>2</sup> K/W (ISO 12664)	
<b>Indoor Air Quality</b>	FloorScore® A+ Emissions	
<b>Underfloor Heating</b>	Suitable, max 27°C (EN 12524)	
<b>Light Stability</b>	Grade 6 (ISO 105-B02:2014)	
<b>Formaldehyde Group</b>	E1 (EN 717-1)	
<b>Classification</b>	Class 23 Domestic Heavy Class 31 Commercial Light	
<b>Warranties</b>	20 Year Residential Warranty 10 Year Commercial Warranty	
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	
<b>Environmental</b>	BREEAM Certified, Greentag Certified Quality Management ISO 9001	



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices