

Protector UV Plus

Construction	Ribbed Needlepunch Carpet
Yarn	100% Polypropylene
Width	2.0m
Standard Roll Length	30m
Yarn Weight	900g/m ²
Total Thickness	6.0mm
Backing	None - Latex Free
Electrical Propensity	≤ 2kV (ISO6356)
Electrical Properties	Antistatic
Fire Rating	Bfl-s1 (EN13501-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
UV Fade Resistance	5000 hours UV stabilized fibre
Use	Indoor / Outdoor
Rating	Medium Duty Commercial
Stair Rating	Suitable
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Reach Compliant Low VOC, solution dying uses no water Quality Management ISO 9001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of
Perfect Choices