

Protector UV

| | |
|----------------------------|---|
| Construction | Ribbed Needlepunch Carpet |
| Yarn | 100% Stainproof Miracle Fibre |
| Width | 2.0m |
| Standard Roll Length | 30m |
| Yarn Weight | 900g/m ² |
| Total Thickness | 9.0mm |
| Backing | Resinbac |
| Electrical Properties | Antistatic |
| Fire Rating | CRF 3.4kW/m ² (ISO 9239-1) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| UV Fade Resistance | 5000 hours UV stabilized fibre |
| Use | Indoor / Outdoor |
| Rating | Extra Heavy Duty Commercial |
| Stair Rating | Suitable |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards. |
| Environmental | Reach Compliant Low VOC, solution dyeing uses no water Quality Management ISO 9001 |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ± 3 mm, Pile Weight ± 5 %.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

**A World of
Perfect Choices** ■