



Construction	Luxury Vinyl Tile
Plank Size	156.97mm x 1242mm
Tiles per Carton	18pcs / 3.51m ²
Total Weight	3846g/m ²
Wearlayer Thickness	0.30mm
Total Thickness	2.0mm
Bevel	0.50mm - 1.0mm micro-bevel
Surface Treatment	Aluminium Oxide
Slip Resistance	R10 (DIN 51130:2014)
Electrical Propensity	<2kV (EN 1815)
Electrical Resistance	ca. 1011 Ohm (EN 1081)
Fire Rating	Bfl-s1 (EN 717-1)
Acoustic Insulation	4dB (EN 140-8)
Dimensional Stability	≤0.12% (EN 434)
Underfloor Heating	Suitable, max 27°C (EN 12524)
Wet Areas	Suitable (ISO 4760:2022)
Residual Indentation	≤0.10mm (EN 434)
Colour Fastness	6 (ISO 105-B02)
Formaldehyde Group	E1 (EN 717-1)
Classifications	Class 23 Domestic Heavy / Class 31 Commercial Light
Warranties	15 Year Residential Warranty / 7 Year Commercial Warranty
Environmental	ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.