

# Puma II

Construction	Finely Ribbed Needle-punch Carpet
Yarn	100% Solution Dyed Olefin
Width	2.0m
Standard Roll Length	75m
Yarn Weight	250g/m <sup>2</sup>
Total Weight	500g/m <sup>2</sup>
Pile Height	1.5mm
Total Thickness	4.0mm
Backing	Foam Back
Electrical Properties	Antistatic
UV Fade Resistance	5000 hours UV stabilized fibre
Use	Indoor
Rating	Residential
Stair Rating	Suitable
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Reach Compliant Low VOC, solution dyeing uses no water Quality Management ISO 9001



- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width  $\pm 3$ mm, Pile Weight  $\pm 5\%$ .
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

**Belgotex**<sup>®</sup>

**A World of  
Perfect Choices** ■