

Category	Laminate
Plank Size	194mm x 1331mm
Planks per Carton	9pcs / 2.324m ²
Weight per Carton	16.8kg
Thickness	8mm
Surface Finishing	Embossed (except Walnut)
Core	HDF
Bevel	Micro-bevel on four sides
Locking System	Angle/Angle
Slip Resistance	DS (EN 14041 / EN 13893)
Thermal Resistance	0.06 m ² K/W (EN 12667)
Fire Rating	Cfl s1 (EN ISO 9239-1)
Indoor Air Quality	A+ Emissions
Formaldehyde Group	E1 (EN 717-1)
Abrasion Resistance	AC5 (EN 13329)
Castor Chair Resistance	No damage with Type W (EN 425)
Impact resistance	IC 2 (EN 13329)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Rating	Domestic Heavy Commercial Medium (Hallways, Classrooms, Small/Medium Offices, Hotels and Retail Stores)
Stair Rating	Suitable
Warranties	20 Year Residential Warranty 5 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
Installation	Must be properly installed according to the installation instructions.
Environmental	EU Ecolabel Cradle to Cradle Environmental Product Declaration LEED® BREEAM Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.