



Stain Resistant



Fade Resistant



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Castor Chair Compatible



Construction	Tip-Sheared Patterned Loop Pile
Yarn	100% Solution Dyed Nylon
Size	304.8mm x 1219.2mm
Tiles per Carton	18pcs / 6.7m <sup>2</sup>
Yarn Weight	1080g/m <sup>2</sup>
Pile Height	3.9mm
Total Thickness	5.5mm
Machine Gauge	5/64
Primary Backing	100% Synthetic
Secondary Backing	Infinity Modular
Electrical Properties	Antistatic
Electrical Propensity	<3.0kv
Fire Rating	CRF 7.7 kW/m <sup>2</sup> (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant
Environmental	GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dying uses no water ISO 14001
Installation	Laying recommendation: 3-Step Verticle Ashlar or Herringbone. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.