



Stain Proof



Fade Proof



Environmentally Responsible



Antistatic



Extra Wide  
4 Metres



Suitable For  
Underfloor Heating



Suitable For  
Stairs



Anti-Allergenic



20 Year  
Premium  
Warranty



GreenTag  
Certified



GreenStar



Homestar



Well  
Building  
Standard

<b>Construction</b>	Level Cut Loop Broadloom Carpet
<b>Yarn</b>	100% Premium Solution Dyed Nylon
<b>Width</b>	4.0m
<b>Pattern Repeat</b>	± W 95cm x L 77cm
<b>Yarn Weight</b>	900g/m <sup>2</sup> / 26.5oz/yd <sup>2</sup>
<b>Total Weight</b>	±1860g/m <sup>2</sup>
<b>Pile Height</b>	6.5mm
<b>Total Thickness</b>	9.0mm
<b>Machine Gauge</b>	1/10th
<b>Primary Backing</b>	Woven Polypropylene
<b>Secondary Backing</b>	FusionBac
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	< 2kV (EN 14041)
<b>Fire Rating</b>	TBC
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Underfloor Heating</b>	Suitable
<b>Rating</b>	Extra Heavy Duty Residential / Medium Duty Commercial
<b>Stair Rating</b>	Suitable
<b>Warranties</b>	<p><b>20 Year Premium Warranty</b></p> <p>20 Year Residential Wear Warranty</p> <p>20 Year Stain Proof Warranty</p> <p>20 Year Fade Proof Warranty</p> <p>20 Year Colourfast Warranty</p> <p>5 Year Manufacturing Defects Warranty</p> <p>10 Year Commercial Wear Warranty</p>
<b>Environmental</b>	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water, Eco-Wash™ Treatment, ISO 14001
<b>Installation</b>	<p>Please contact Gilt Edge Industries for all adhesive and installation instructions.</p> <p>NB: If recommended adhesive is not used, claims will not be accepted.</p> <p>All seams must be sealed.</p> <p>Must be laid in accordance with AS/NZ Installation Standards.</p>

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.