Retreat











Construction Tufted Cut Pile Carpet Yarn 100% Solution Dyed Nylon Width 3.66m Standard Roll Length 25m Yarn Weight 1966g/m² / 58oz/yd² Total Weight 2976g/m² Pile Height 14.0mm Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 9001 Occupational Health and Safety Management ISO 45001		
Width 3.66m Standard Roll Length 25m Yarn Weight 1966g/m² / 58oz/yd² Total Weight 2976g/m² Pile Height 14.0mm Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV	Construction	Tufted Cut Pile Carpet
Standard Roll Length 25m Yarn Weight 1966g/m² / 58oz/yd² Total Weight 2976g/m² Pile Height 14.0mm Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty 10 Year Residential Warranty 11 Seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Yarn	100% Solution Dyed Nylon
Yarn Weight 1966g/m² / 58oz/yd² Total Weight 2976g/m² Pile Height 14.0mm Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Width	3.66m
Total Weight 2976g/m² Pile Height 14.0mm Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Standard Roll Length	25m
Pile Height 14.0mm Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV	Yarn Weight	1966g/m² / 58oz/yd²
Total Thickness 16.0mm Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Total Weight	2976g/m²
Machine Gauge 1/8th Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Pile Height	14.0mm
Primary Backing Woven Polypropylene Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV	Total Thickness	16.0mm
Secondary Backing Action Fleece Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Machine Gauge	1/8th
Electrical Properties Antistatic Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty 10 Year Residential Warranty 11 Year Commended adhesive is not used, claims will not be accepted. 12 All seams must be sealed. 13 Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified 15 Low VOC, solution dying uses no water 15 Environmental Management ISO 14001 15 Quality Management ISO 9001	Primary Backing	Woven Polypropylene
Electrical Propensity < 2kV Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Secondary Backing	Action Fleece
Fire Rating CRF 4.8kW/m² (ISO 9239-1) Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 9001	Electrical Properties	Antistatic
Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Electrical Propensity	< 2kV
Underfloor Heating Suitable Stair Rating Suitable Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Fire Rating	CRF 4.8kW/m² (ISO 9239-1)
Stair Rating Suitable Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Rating Extra Heavy Duty Residential Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Underfloor Heating	Suitable
Medium Duty Commercial Warranties 10 Year Residential Warranty 5 Year Commercial Warranty Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Stair Rating	Suitable
Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Rating	
NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. Environmental CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Warranties	
Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001	Installation	NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed.
	Environmental	Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001





- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex

A World of Perfect Choices