

# Roam



<b>Construction</b>	Heterogeneous Sheet Vinyl
<b>Width</b>	2.0m
<b>Standard Roll Length</b>	20m
<b>Pattern Repeat</b>	1460g/m <sup>2</sup> / 43oz/yd <sup>2</sup>
<b>Total Weight</b>	2810g/m <sup>2</sup>
<b>Wearlayer Thickness</b>	0.7mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	PUR Treatment
<b>Slip Resistance</b>	R10 (DIN 51130)
<b>Electrical Propensity</b>	<2kV (EN 1815)
<b>Fire Rating</b>	CRF 10.7kW/m <sup>2</sup> (EN ISO 9239-1)
<b>Acoustic Insulation</b>	3dB (EN ISO 10140)
<b>Wear Group</b>	T (EN 660-2)
<b>Dimensional Stability</b>	< 0.4kV (EN ISO 23999)
<b>Thermal Insulation</b>	.0128m <sup>2</sup> k/w (EN 12664)
<b>Indoor Air Quality</b>	TVOC after 28 days <100 µg/m <sup>3</sup> (ISO 16000-6)
<b>Underfloor Heating</b>	Suitable
<b>Residual Indentation</b>	<0.1mm (EN ISO 24343-1)
<b>Colour Fastness</b>	≥6 (EN ISO 105-B02)
<b>Classification</b>	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
<b>Warranty</b>	15 Year Residential Warranty 10 Year Commercial Warranty
<b>Environmental</b>	Floorscore Environmental Product Declaration A+ Emissions
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices