

Sérénité



Construction	Tufted Saxony Cut Pile Carpet
Yarn	100% Regenerated Econyl Solution Dyed Nylon
Width	4.0m
Yarn Weight	1100g/m ²
Total Weight	2110g/m ²
Pile Height	6.1mm
Total Thickness	8.5mm
Machine Gauge	1/10th
Backing	Action Back
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 9.8kW/m ² (ISO 9239-1)
VOC Rating	A+ (AGBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 28dB (ISO 140-8)
Acoustic Absorption	αw 0.20 (ISO 11654)
Underfloor Heating	Suitable
Stair Rating	Suitable
Luxury Class	LC4
Rating	Heavy Duty Commercial
Warranties	15 Year Residential Warranty 15 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Label, LEED® CRI Green Label Certified Recycled Fibre, 100% Green Electricity Low VOC, Solution dyeing uses no water Environmental Product Declaration Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices