Shuffl.

Construction	Patterned Tufted Loop Pile
Yarn	100% Stainproof SDX (Solution dyed nylon)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m²
Pile Weight	650g/m²
Total Weight	2520g/m²
Pile Height	± 5.5mm
Total Thickness	± 7.5mm
Machine Gauge	1/10th
Backing	ProBac (comfort backing)
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV (ISO 6356:2012)
Fire Rating	CRF 8.1kW/m² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 26dB (EN ISO 10140:2021)
Acoustic Absorption	αω 0.25 (EN/ISO 354:2003)
Colour Fastness	Light > 6.0 (NF EN ISO 105-BO2) Rubbing (staining) 4-5 (ISO 105-X12) Water (staining) 4-5 (ISO 105-EO1)
Underfloor Heating	Suitable
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Installation	Laying recommendation: Monolithic Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GreenTag Product Health Declaration (PHD) Platinum Health Certified Low VOC, Solution dying uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices