



Stain Resistant



Fade Resistant



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Castor Chair Compatible



|                            |                                                                                                                                                                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction               | Textured Patterned Loop Pile                                                                                                                                                                                                                                                    |
| Yarn                       | 100% Solution Dyed Nylon                                                                                                                                                                                                                                                        |
| Size                       | 304.8mm x 1219.2mm                                                                                                                                                                                                                                                              |
| Tiles per Carton           | 18pcs / 6.7m <sup>2</sup>                                                                                                                                                                                                                                                       |
| Yarn Weight                | 814g/m <sup>2</sup>                                                                                                                                                                                                                                                             |
| Pile Height                | 2.7mm                                                                                                                                                                                                                                                                           |
| Total Thickness            | 4.4mm                                                                                                                                                                                                                                                                           |
| Machine Gauge              | 5/64                                                                                                                                                                                                                                                                            |
| Primary Backing            | 100% Synthetic                                                                                                                                                                                                                                                                  |
| Secondary Backing          | Infinity Modular                                                                                                                                                                                                                                                                |
| Electrical Properties      | Antistatic                                                                                                                                                                                                                                                                      |
| Electrical Propensity      | <3.0kv                                                                                                                                                                                                                                                                          |
| Fire Rating                | CRF 7.4 kW/m <sup>2</sup> (ISO 9239-1)                                                                                                                                                                                                                                          |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.                                                                                                                                                                                                                             |
| Classification             | Heavy Duty Commercial                                                                                                                                                                                                                                                           |
| Stair Rating               | Suitable                                                                                                                                                                                                                                                                        |
| Warranty                   | <b>15 Year Commercial Warranty</b><br>Limited Lifetime Wear & Backing<br>Limited 15-Year Xguard Stain Resistant<br>Limited 15-Year ColorSafe Bleach Resistant                                                                                                                   |
| Environmental              | GreenStar, Homestar™, LEED®<br>Well Building Standard®<br>CRI Green Label Plus Certified<br>Environmental Product Declaration<br>Contains Recycled content<br>Low VOC, solution dying uses no water<br>ISO 14001                                                                |
| Installation               | Laying recommendation: 3-Step Verticle Ashlar.<br>Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.