

Sonoma



Construction	Tufted Cut Pile Carpet
Yarn	100% Premium Solution Dyed Nylon
Width	4.0m
Standard Roll Length	25m
Yarn Weight	1580g/m ² / 46oz/yd ²
Total Weight	2750g/m ²
Pile Height	10.0mm
Total Thickness	12.0mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1307 / ISO 6356)
Fire Rating	CRF 4.5kW/m ² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Stair Rating	Suitable
Rating	Extra Heavy Duty Residential Medium Duty Commercial
Warranties	15 Year Residential Warranty 7 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified GreenStar, Homestar™ WELL Building Standard® Product Health Declaration™ Eco-Wash™ Treatment Low VOC, Solution dyeing uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices