



Stain Resistant



Fade Resistant



Antistatic



Suitable For
Underfloor Heating



15 Year
Commercial
Warranty



Construction	Textured Loop Pile
Yarn	100% Regenerated Solution Dyed ECONYL Nylon
Size	500mm x 500mm
Tiles per Carton	16pcs / 4.0m ²
Yarn Weight	850g/m ²
Total Weight	5000g/m ²
Pile Height	3.5mm
Total Thickness	7.9mm
Machine Gauge	1/10
Primary Backing	Non-Woven PVC Free
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	Bfl-S1 (EN 14041)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	27dB (ISO 140-8)
Acoustic Absorption	α _w 0.20 (ISO 11654)
Dimensional Stability	≤ 0.20% (EN 986)
Thermal Insulation	< 0.15m ² C° /W
Underfloor Heating	Suitable
Colour Fastness	> 7/8 on Grey Scale
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar, Homestar™, Well building Standard® Gut Label Certified, LEED® CRI Green Label Certified Environmental Product Declaration 100% Green Electricity Low VOC, Contains recycled content ISO 14001
Installation	Laying recommendation: Monolithic or Quarter Turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.