

Category	European Hardened Timber
Plank Size	233mm x 2050mm
Planks per Carton	5pcs / 2.388 m ²
Weight per Carton	16.71kg
Thickness	10mm
Top Layer Thickness	0.6mm
Surface Finishing	Super Matt
Bevel	Microbevelled 4-sided
Core	HDF
Locking System	Unifit X
Slip Resistance	Dry USRV 62.25 Wet USRV 47.75 (CE / TS 15676:2008 / EN 14342:2013)
Thermal Resistance	0.073 m ² K/W (EN 12667)
Thermal Conductivity	0.14 W/mK (EN 12667)
Fire Rating	Cfl-s1 (EN13501-1)
Indoor Air Quality	Floorscore A+ Emissions
Formaldehyde Group	E1 (EN 717-1)
Wear Resistance	> 6000 Cycles (EN14354)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Classification	Class 23 Domestic Heavy Class 33 Commercial Heavy
Stair Rating	Suitable
Warranties	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
Installation	Must be properly installed according to the installation instructions.
Environmental	Forest Stewardship Council (FSC) Environmental Product Declaration LEED Certified Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.