

# Taralay Impression Acoustic



<b>Construction</b>	Heterogeneous Sheet Vinyl
<b>Width</b>	2.0m
<b>Standard Roll Length</b>	25m
<b>Total Weight</b>	2825g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	0.65mm
<b>Total Thickness</b>	3.35mm
<b>Surface Protection</b>	Protecsol®
<b>Slip Resistance - Oil Pendulum</b>	R10 (DIN 51130)
<b>Slip Resistance - Wet Pendulum</b>	P5 (AS 4586-2013, App A)
<b>Electrical Propensity</b>	≤ 2kV (EN 1815)
<b>Fire Rating</b>	CRF 8.1kW/m <sup>2</sup> (ISO 9239-1)
<b>Acoustic Insuation</b>	19dB (ISO 717-2)
<b>Wear Resistance</b>	≤2mm <sup>3</sup> (EN 660.2)
<b>Wear Group</b>	T (NF 189)
<b>Dimensional Stability</b>	≤0.40% (EN ISO 23999, EN 434)
<b>Thermal Insulation</b>	0.25W/mK (ISO 10456)
<b>Indoor Air Quality</b>	TVOC after 28 days <10µg/m <sup>3</sup> (ISO 16000-6) FloorScore®
<b>Anti-bacterial Activity (E. coli - S. aureus – MRSA)</b>	> 99% inhibits growth (ISO 22196)
<b>Residual Indentation (requirement)</b>	≤0.20mm (EN ISO 24343-1, EN 433)
<b>Residual Indentation (average value measured)</b>	≈0.08mm
<b>Colour Fastness</b>	≥6 (EN 20 105 - B02)
<b>Chemical Resistance</b>	OK (EN ISO 26987)
<b>Classification</b>	Class 34 Commercial Very Heavy Class 42 Industrial Medium
<b>Warranties</b>	12 Year Commercial Warranty
<b>Installation</b>	Random Repeat, Reverse Sheet for Seaming (except for wood and ceramic designs). Cove Fillet or Pencil Cove is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	Greentag Certified



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

## Belgotex®

## A World of Perfect Choices