

Tarasafe H20



Construction	Multi-Layered Sheet Vinyl
Width	2.0m
Standard Roll Length	20m
Pattern Repeat	Random repeat, directional laying
Total Weight	2350g/m ²
Wear Layer Thickness	0.85mm
Total Thickness	2.0mm
Slip Resistance - Oil Wet Ramp	R11 (AS 4586-2013, App D)
Slip Resistance - Wet Pendulum	P5 (AS 4586-2013, App A)
Slip Resistance - Wet/Barefoot Ramp	B (AS 4586-2013, App C)
Surface Roughness Rtm	Rz ≥20 µm
Electrical Propensity	< 2kV (EN 1815)
Fire Rating	CRF 8.9kW/m ² (ISO 9239-1)
Wear Resistance	≤4mm ³ (EN 660.2)
Wear Group	T (EN 651)
Dimensional Stability	≤0.40% (EN 434)
Thermal Insulation	0.25W/mK (EN ISO 10456, EN 12524)
Indoor Air Quality	0.266mg/m ² /hr (24hours, ASTM D5116) FloorScore®
Residual Indentation	≤0.10mm (EN 433)
Colour Fastness	≤6 (EN 20 105 - B02)
Chemical Resistance	Good (EN 423)
Classification	Class 34 Commercial Very Heavy Class 43 Industrial Heavy
Warranties	12 Year Commercial Warranty
Installation	Random Repeat, Reverse Sheet for Seaming Cove Fillet or Pencil Cove is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	100% Recyclable Greentag Certified



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

Belgotex®

A World of Perfect Choices