Tarasafe Standard PUR

Gerflor theflooringgroup | Belgotex

Suitable For Underfloor Heating | Antistatic | Environmentally Responsible | 100% Recyclable | R10 Slip Restraint

Construction	Multi-Layered Sheet Vinyl
Width	2.0m
Standard Roll Length	20m / 40m²
Pattern Repeat	Random repeat, directional laying.
Total Weight	2460g/m²
Wearlayer Thickness	0.85mm
Total Thickness	2.0mm
Slip Resistance - Wet Pendulum	P4 (AS 4586:2013, App A)
Slip Resistance - Oil Wet Ramp	R10 (AS/NZS 4586:2004, App D)
Surface Roughness Rtm	Rz ≥20 µm
Electrical Propensity	<2kV (EN 1815)
Fire Rating	CRF 8.9kW/m² (ISO 9239-1)
Wear Resistance	≤2mm³ (EN 660.2)
Wear Group	T (NF 189)
Type Binder Content	I (EN ISO 10582)
Dimensional Stability	≤0.40% (EN ISO 23999, EN 434)
Thermal Insulation	0.25W/mK (EN ISO 10456, EN 12524)
Indoor Air Quality	TVOC after 28 days <100µg/m³ (ISO 16000-6) FloorScore®
Anti-bacterial Activity (MRSA)	> 99% inhibits growth (ISO 22196)
Residual Indentation	≤0.05mm (EN ISO 24343-1, EN 433)
Colour Fastness	≥6 (EN 20 105 - B02)
Chemical Resistance	OK (EN ISO 26987, EN 423)
Classifications	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
Warranty	12 Year Commercial Warranty
Environmental	100% Recyclable, Greentag Certified
Installation	Random Repeat, Reverse Sheet for Seaming Cove Fillet or Pencil Cove is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.