



Construction	Tufted Hi Low Infinity Loop Pile	
Yarn	100% Stainproof SDX (Solution Dyed Nylon)	
Size	500mm x 500mm	
Tiles per Carton	20pcs / 5.0m ²	
Pile Weight	± 660g/m ²	
Total Weight	± 2666g/m ²	
Pile Height	5.0mm	
Total Thickness	± 7.7 - 8.8mm	
Machine Gauge	1/10th	
Primary Backing	Nonwoven Polyester	
Backing	ProBac (comfort backing)	
Impact Sound Reduction	ΔLw 27dB (EN ISO 10143-3)	
Sound Absorption	α _w 0.25 (EN ISO 354)	
Thermal Resistance	0.1283m ² K/W	
Electrical Properties	Antistatic	
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)	
Fire Rating	CRF 8.4 kW/m ² (ISO 9239-1)	
VOC Rating	Pass (GBCSA/GLP Criteria)	
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.	
Underfloor Heating	Suitable	
Colour Fastness	Light	>6.0 (ISO 105 - B02)
	Rubbing	Wet 4-5 (ISO 105 - X12) Dry 4-5 (ISO 105 - X12)
	Water	4-5 (ISO 105 - E01)
Rating	Class 33 Commercial Heavy	
Stair Rating	Suitable	
Warranties	15 Year Commercial Warranty	
Installation	Laying recommendation: Quarter Turn Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	

Environmental

GreenTag Product Health Declaration (PHD) Platinum Health Certified
 Low VOC, Solution dying uses no water
 Quality Management ISO 9001
 Environmental Management ISO 14001
 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices