

# Vault



<b>Construction</b>	Heterogeneous Sheet Vinyl
<b>Width</b>	2.0m
<b>Standard Roll Length</b>	22m
<b>Total Weight</b>	2800g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	0.7mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	PU Lacquer
<b>Slip Resistance</b>	R10 (DIN 51 130)
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	≤ 2kV (EN 1815)
<b>Fire Rating</b>	CRF 9.0kW/m <sup>2</sup> (ISO 9239-1)
<b>Acoustic Insulation</b>	ΔLw 6dB (ISO 717/2)
<b>Wear Group</b>	T (EN 660-2)
<b>Curling</b>	≤8mm (EN ISO 23999)
<b>Dimensional Stability</b>	≤0.40% (EN 434)
<b>Thermal Insulation</b>	0.14W/m/K (EN 12524)
<b>Indoor Air Quality</b>	FloorScore®
<b>Underfloor Heating</b>	Suitable
<b>Residual Indentation</b>	≤0.1mm (EN ISO 24343-1, EN 433)
<b>Colour Fastness</b>	≥6 (EN 20 105 - B02)
<b>Chemical Resistance</b>	OK (ISO 26987, EN 423)
<b>Classification</b>	Class 34 Commercial Very Heavy Class 43 Industrial Heavy
<b>Warranties</b>	15 Year Residential Warranty 10 Year Commercial Warranty
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	100% Recyclable 100% Phthalate Free



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

# Belgotex®

## A World of Perfect Choices