

Venus



Construction	Tufted Loop Pile Carpet
Yarn	100% Wool
Yarn Specification	4-ply yarn, stock dyed, felted
Width	4.0m
Standard Roll Length	30m
Yarn Weight	2050g/m ² / 60.5oz/yd ²
Total Weight	3347g/m ²
Pile Height	8.5mm
Total Thickness	13.5mm
Machine Gauge	1/2"
Primary Backing	Synthetic woven fabric
Secondary Backing	Action Bac
Electrical Properties	Antistatic
Fire Rating	Cfl-s1, CRF ≥ 4.5 kW/m ² (EN 13501-1, ISO 9239-1)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Rating	Heavy Duty Residential Light Duty Commercial
Stair Rating	Suitable
Warranties	10 Year Residential Warranty 5 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Certified, Low VOC, EN 14041



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices