

# Decoprint

<b>Description</b>	Decoprint Protection Panel with Customized Digital Printing
<b>Thickness</b>	±1.0mm +/- 0.15mm
<b>Width</b>	1200mm maximum
<b>Length</b>	2900mm maximum
<b>Weight</b>	1400g/m <sup>2</sup> +/-200
<b>Density</b>	1.40g/cm <sup>3</sup>
<b>Stabilization</b>	CaZn
<b>Design Options</b>	11 Designs available in predefined colours
<b>Surface</b>	Textured
<b>Fire Rating</b>	B-s2,d0 (EN 13501-1)
<b>Chemicals resistance</b>	Anios compliant H2O2 compliant
<b>Decontamination of surface (radionuclide)</b>	Excellent (ISO 8690)
<b>Anti-bacterial activity (2) (S. aureus – S. pyogenes)</b>	> 99% inhibits growth (ISO 22196)
<b>Indoor Climate</b>	TVOC after 28 days < 15µg/m <sup>3</sup> (ISO 16000-6) A+ Emissions, Greenguard Gold label
<b>Installation</b>	Please see our website for installation instructions. NB: If the recommended installation is not followed, claims will not be accepted.
<b>Environmental</b>	100% REACH Compliant 100% Recyclable



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

**Belgotex**<sup>®</sup>

**A World of  
Perfect Choices**