Winter

Construction	Loop Pile Carpet Tile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	24pcs / 6.0m²
Pile Weight	540g/m²
Total Weight	3955g/m²
Pile Height	2.3mm
Total Thickness	5.5mm
Machine Gauge	1/10th
Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 8.3kW/m² (ISO 9239-1)
VOC Rating	A+ (AGBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 24dB (ISO 140-8)
Acoustic Absorption	αω 0.15 (ISO 11654)
Dimensional Stability	<0.20% (EN986)
Thermal Insulation	<0.15%m²C°/W
Underfloor Heating	Suitable
Colour Fastness	>7/8 on Grey Scale (ISO105-B02)
Luxury Class	LC1
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Installation	Laying recommendation: Monolithic or Quarter Turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Label, LEED®, BREEAM CRI Green Label Certified 100% In Face Fibre Low VOC, Contains recycled fibre Environmental Product Declaration Quality Management ISO 9001 Environmental Management ISO 14001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices