
## Belgotex

112

182



190

















## GLOBE





















Construction	Tufted Loop Pile Carpet
Yarn	50% Pure Wool, 50% Polypropylene
Yarn Specification	3-ply yarn, stock dyed
Width	4.0m & 5.0m
Standard Roll Length	30m
Yarn Weight	1100g/m² / 32.4oz/yd²
Total Weight	2125g/m²
Pile Height	4.9mm
Total Thickness	7.9mm
Machine Gauge	5/32"
Backing	Action Bac
Fire Test	ISO 9239-1
Insect Resistance	Treated against insect and moth infestation.
Thermal Conductivity	0.14 m <sup>2</sup> / K/W
Underfloor Heating	Suitable
Luxury Class	LC 3
Rating	Class 23 Domestic Heavy / Class 31 Commercial Light
Warranties	15 Year Best Wool Warranty Including: Lifetime Manufacturing Defects Warranty 5 Year Insect Resistance Warranty
Environmental	GUT Certified, Low VOC, EN 14041
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions.  NB: If recommended adhesive is not used, claims will not be accepted.

All seams must be sealed.

Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
 Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
 Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Must be laid in accordance with AS/NZ Installation Standards.