

CARPET

[BPIR Disclosure Statement - Broadloom Carpet](#)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
Africa Premium Wool	4.0m	1200g/m ² / 36oz/yd ²	Wool	Action Bac	SH Risk Group Only	Alternative EN 14041	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
Alexandria Textured SDN	4.0m	1460g/m ² / 43oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Alinea Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Amiral Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Amoré Textured SDN	3.66m	2220g/m ² / 66oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 6.3kW/m ²	Acceptable D1/AS1,2.1.2(b)
Aqua Territoires	4.0m	1240g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Verification Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
Aqua Textured Premium SDN	4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Atrium Territoires	4.0m	1240g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Verification Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
Avenue SDN	3.66m	1260g/m ² / 37oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 3.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Ayrton	3.66m	1260g/m ² / 37oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 3.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Ballan	3.66m	1560g/m ² / 46oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.0kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range		Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
							Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
Baltimore	□	4.0m	1200g/m ² / 36oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 4.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Bark II TxStyle	□	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Bases Loaded Polyester	□	3.66m	1010g/m ² / 30oz/yd ²	SDPET	Action Fleece	SH Risk Group Only	Alternative ISO 9001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
Belleville Premium Wool	□	4.0m	1695g/m ² / 50oz/yd ²	Wool	Action Bac	All Building Types	Alternative EN 14041	Verification Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
Bohème Vision of Elegance	□	4.0m	1250g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Boulevard SDN	□	3.66m	1560g/m ² / 46oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
Bradbury Poetica	□	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Bravo Stainproof SDN	□	4.0m	1600g/m ² / 48oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 2.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Bridge Les Best Design II	□	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Brio	□	4.0m	1525g/m ² / 45oz/yd ²	SDN	Fusionbac	SH Risk Group Only	Alternative ISO 9001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
Camus Poetica	□	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Canopy II TxStyle	□	3.66m	746g/m ² / 22oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 9.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
Carrare Les Best Design II	□	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Carroll Poetica	□	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
<u>César</u> French Couture	4.0m	1050g/m ² / 31oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Chevron</u> <u>Textured Premium SDN</u>	4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Chicago</u> <u>SDN</u>	3.66m	880g/m ² / 26oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Circ</u> Vivendi	3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 9.1kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Circuit</u>	3.66m	678g/m ² / 20oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 7.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Cirro Heights</u> <u>Polyester</u>	3.66m	2300g/m ² / 67oz/yd ²	SDPET	Woven Mesh Backing	SH Risk Group Only	Alternative EN 14001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
<u>Classic Choice</u> <u>Polyester</u>	3.66m	1600g/m ² / 48oz/yd ²	SDPET	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 2.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Co-exist</u>	4.0m	780g/m ² / 23oz/yd ²	SDPP	Fusionbac	SH Risk Group Only	Alternative ISO 9001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
<u>Conscious</u>	4.0m	1200g/m ² / 32.5oz/yd ²	SDPP	Fusionbac	SH Risk Group Only	Alternative ISO 9001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
<u>Copenhagen</u> <u>Premium Wool</u>	4.0m	1280g/m ² / 38oz/yd ²	Wool	Jute	All Building Types	Alternative EN 14041	Verification Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
<u>Crammond</u>	3.66m	2250g/m ² / 66oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Crescent</u> <u>SDN</u>	3.66m	2250g/m ² / 66oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Cubed</u> <u>Textured Premium SDN</u>	-	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Delta</u> <u>Stainproof SDN</u>	4.0m	1200g/m ² / 36oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 5.6kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
Domain SDN	□ 3.66m	1490g/m ² / 44oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.6kW/m ²	Acceptable D1/AS1,2.1.2(b)
East Street	□ 3.66m	1153g/m ² / 34oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Echo Les Best Design II	□ 4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Empire SDN	□ 3.66m	1200g/m ² / 36oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Encre Unique Territoire	□ 4.0m	1240g/m ² / 37oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Encre Dalle Unique Territoire	□ -	-	-	-	-	-	-	-
Enzo SDN	□ 3.66m	880g/m ² / 26oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 2.6kW/m ²	Acceptable D1/AS1,2.1.2(b)
Exposed	□ 4.0m	1200g/m ² / 36oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 2.9kW/m ²	Acceptable D1/AS1,2.1.2(b)
Fan Fold Origami	□ 3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Fifth Avenue	□ 3.66m	1831g/m ² / 54oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.9kW/m ²	Acceptable D1/AS1,2.1.2(b)
Fitzgerald Poetica	□ 3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
Forest Grove Stainproof SDN	□ 4.0m	1000g/m ² / 30oz/yd ²	SDN	FusionBac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.9kW/m ²	Acceptable D1/AS1,2.1.2(b)
Fortress	□ 4.0m	700g/m ² / 21oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Galway	□ 4.0m	1600g/m ² / 48oz/yd ²	SDN	Cosyback	All Building Types	Alternative ISO 9001	Acceptable CRF 3.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
Gaskell Poetica	□ 3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.7kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
<u>Gina</u> French Couture	4.0m	1050g/m ² / 31oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Grandor</u>	4.0m	1600g/m ² / 48oz/yd ²	SDN	Cosyback	All Building Types	Alternative ISO 9001	Acceptable CRF 3.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Graph</u> Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Haven</u> <u>SDN</u>	3.66m	1080g/m ² / 32oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Hilton</u> <u>Premium SDN</u>	4.0m	2000g/m ² / 59oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Husk</u> Entwined	3.66m	746g/m ² / 22oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 8.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Ilda</u> French Couture	4.0m	1050g/m ² / 31oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Immerse</u>	4.0m	1020g/m ² / 30oz/yd ²	SDPP	Fusionbac	SH Risk Group Only	Alternative ISO 9001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
<u>Irving</u> Poetica	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Kabuki</u> Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Kathmandu</u> <u>Premium Wool</u>	4.0m	2050g/m ² / 60oz/yd ²	Wool	Jute	SH Risk Group Only	Alternative EN 14041	Acceptable Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
<u>Kipling 3</u> Poetica	3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Léon</u> French Couture	4.0m	1050g/m ² / 31oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Les Best</u>	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
Lewis Poetica □	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Lhasa Premium Wool □	4.0m	1480g/m ² / 43oz/yd ²	Wool	Action Bac	All Building Types	Alternative EN 14041	Verification Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
Liberty SDN □	3.66m	900g/m ² / 26.5oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 6.1kW/m ²	Acceptable D1/AS1,2.1.2(b)
Lily French Couture □	4.0m	1050g/m ² / 31oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Lusso SDN □	3.66m	1220g/m ² / 36oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 3.3kW/m ²	Acceptable D1/AS1,2.1.2(b)
Maiden Lane □	3.66m	1492g/m ² / 44oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Majestic □	4.0m & 5.0m	1300g/m ² / 38oz/yd ²	Wool	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 10.8kW/m ²	Acceptable D1/AS1, 2.1.2(b)
Mamurah Textured SDN □	4.0m	1290g/m ² / 38oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 5.3kW/m ²	Acceptable D1/AS1,2.1.2(b)
Mesh Textured Premium SDN □	4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Mesh Carpet Tiles □ Urban Grid	3.66m	542g/m ² / 16oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.6kW/m ²	Acceptable D1/AS1,2.1.2(b)
Mikado □ Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Mindful □	4.0m	1020g/m ² / 30oz/yd ²	SDPP	Fusionbac	SH Risk Group Only	Alternative ISO 9001	Acceptable C/AS1 No Requirements	Acceptable D1/AS1,2.1.2(b)
Montage Vivendi □	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 9.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Montgomery Poetica □	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
Moroccan Berber Textured SDN	4.0m	1055g/m ² / 31oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 4.9kW/m ²	Acceptable D1/AS1,2.1.2(b)
Moso Entwined	3.66m	746g/m ² / 22oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 8.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Napa Valley Premium SDN	4.0m	2060g/m ² / 60oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 4.4kW/m ²	Acceptable D1/AS1,2.1.2(b)
Orwell Poetica	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Oscar French Couture	4.0m	1050g/m ² / 31oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Palazzo	4.0m	1600g/m ² / 48oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 3.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
Parkview Gardens Stainproof SDN	4.0m	1200g/m ² / 36oz/yd ²	SDN	FusionBac	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Poesie Vision of Elegance	4.0m	1250g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Pompadour Vision of Elegance	4.0m	1250g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Premio SDN	3.66m	1595g/m ² / 47oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 3.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Raffia	3.66m	712g/m ² / 21oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 8.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
Ramie Entwined	3.66m	746g/m ² / 22oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 8.4kW/m ²	Acceptable D1/AS1,2.1.2(b)
Relic Textured Premium SDN	4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Retreat SDN	3.66m	1966g/m ² / 58oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 4.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Riverside Reserve Stainproof SDN	4.0m	1800g/m ² / 53oz/yd ²	SDN	FusionBac	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
Rockefeller SDN	□ 3.66m	1800g/m ² / 53oz/yd ²	SDN	Action Fleece	All Building Types	Alternative ISO 9001	Acceptable CRF 8.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
Romance Vision of Elegance	□ 4.0m	1250g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Rossetti 2 Poetica	□ 3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Scaffold Urban Grid	□ 3.66m	542g/m ² / 16oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.3kW/m ²	Acceptable D1/AS1,2.1.2(b)
Scales Textured Premium SDN	□ 4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
School	□ 3.66m	500g/m ² / 15oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 2.3kW/m ²	Acceptable D1/AS1,2.1.2(b)
Schubert Poetica	□ 3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Serengeti	□ 4.0m	1200g/m ² / 36oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 8.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
Sérénité	□ 4.0m	1100g/m ² / 32oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
Smart Vision of Elegance	□ 4.0m	1250g/m ² / 37oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
Softer Sisal Premium Wool	□ 4.0m	1280g/m ² / 38oz/yd ²	Wool	Jute	All Building Types	Alternative EN 14041	Verification Cfl-s1 (EN 13501)	Acceptable D1/AS1,2.1.2(b)
Softology- S301	□ 4.0m	1650g/m ² / 49oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 2.4kW/m ²	Acceptable D1/AS1,2.1.2(b)
Somerset Poetica	□ 3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.7kW/m ²	Acceptable D1/AS1,2.1.2(b)
Sonoma Premium SDN	□ 4.0m	1580g/m ² / 46oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
Squareberry II TxStyle	□ 3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)

Range	Width	Weight	Yarn	Backing	Scope of Use	Building Code Compliance		
						Durability B2.3.1(c)	Fire Spread C3.4(b)	Access Routes D1.3.3
<u>Stravinsky</u> Poetica	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Sublime</u>	4.0m	1430g/m ² / 42.20oz/yd ²	SDN	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 8.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Swing</u> Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Swirl</u> <u>Textured Premium SDN</u>	4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Tango</u> <u>Stainproof SDN</u>	4.0m	800g/m ² / 24oz/yd ²	SDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 5.2kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Teres</u> Vivendi	3.66m	780g/m ² / 23oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Tulle</u> <u>Textured Premium SDN</u>	4.0m	900g/m ² / 26.5oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 6.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Tweed</u> Les Best Design II	4.0m	1200g/m ² / 36oz/yd ²	Nylon	Action Back	All Building Types	Alternative ISO 9001	Acceptable CRF 9.8kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Venus</u> <u>Premium Wool</u>	-	-	-	-	-	-	-	-
<u>Vivaldi</u> Poetica	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 4.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Westminster</u> <u>Premium SDN</u>	4.0m	1200g/m ² / 36oz/yd ²	PSDN	Fusionbac	All Building Types	Alternative ISO 9001	Acceptable CRF 3.0kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Whitman</u> Poetica	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)
<u>Yeats 3</u> Poetica	3.66m	814g/m ² / 24oz/yd ²	SDN	Integra HP	All Building Types	Alternative ISO 9001	Acceptable CRF 5.5kW/m ²	Acceptable D1/AS1,2.1.2(b)